

55x124,3x92 HUO-18 IP 00

58x146,2x111,7 HUO-32 IP 00

69x150,5x111,7 HUO-40 IP 00

93x219,3x123 HUO-65 IP 00

88x160x94 HUE-11 IP 40

88x160x107,5 HUEB-11 IP 40

90x184x112 HUFB-18 IP 65

Note: UPAC also supplies Star-Delta Starters

Catalogue number				DPA-3020	DPA-3025	DPA-3030	DPA-3040
Photos				 62x95.3x73.9	 62x95.3x73.9	 62x95.3x73.9	 62x95.3x73.9
Number of poles				3	3	3	3
Terminal				SCREW / LUG	SCREW / LUG	SCREW / LUG	SCREW / LUG
Rated Insulation Voltage (Ui) UL/IEC				600/660			
Operation Voltage (Ue) UL/IEC				600/660			
Duty thermal current (Ith) UL/IEC				30	35	40	50
AIR-CONDITIONING & REFRIGERATION INSTITUTE Standard 780/790	Full load amps (FLA)		20	25	30	40	
	Locked rotor amps (LRA) A	Single Phase	240/277V	120	150	180	240
		Three Phase	480V	100	125	150	200
			600V	80	100	120	160
	Resistance Load (RES) A		30	35	40	50	
UL 508	Full Load current (FLA)	Single Phase	120V	1.5Hp/20A	2Hp/24A	2Hp/24A	3Hp/34A
			240/277V	3Hp/17A	5Hp/28A	5Hp/28A	7.5Hp/40A
			440/480V	5Hp/14A	5Hp/14A	7.5Hp/21A	15Hp/34A
			220/240V	7.5Hp/22A	10Hp/28A	10Hp/28A	10Hp/28A
			440/480V	7.5Hp/11A	15Hp/21A	15Hp/21A	20Hp/27A
			550/600V	7.5Hp/9A	20Hp/22A	20Hp/22A	25Hp/27A
			IEC 60947-1 IEC 60947-4-1 AC 7a, AC 8a	Rated current (A)	220V	20	25
380V	20	25			30	40	
Resistance Load (RES) A		32		35	40	50	
Weight (kg)				0.43	0.43	0.43	0.43

Notes : 1. DPA—3 Pole standard type with Top cover and anti dust cover.
2. DPA—3 Pole add on side mounting aux is 3 N/C (max).
3. DPA—3 Pole can provide reversing type.

http://www.upac.com.tw
E-mail: upac@seed.net.tw